

Silicon Nitride (Si₃N₄)

Performance parameters of silicon nitride

Material Properties	Unit	Silicon Nitride
Density	g/cm ³	3.2
Vickers hardness	GPa	15
Bending strength	MPa	1000
Compressive strength	MPa	3000
Elastic modulus	GPa	320
Toughness	MPa·m ^{1/2}	8
Poisson's ratio	—	0.26
Young's Modulus	GPa	320

Thermal Properties	Unit	Silicon Nitride
Thermal conductivity	W/mK	25
melting point	°C	1900
Specific heat capacity	J/g·K	0.71
linear expansion coefficient	10 ⁻⁶ /K	3.2
Maximum operating temperature	°C	1400

JUNDRO

Electrical Properties	Unit	Silicon Nitride
Dielectric constant	1 MHz	8
Breakdown voltage	V/cm	> 10 ⁶
Dielectric loss	1 MHz	0.001
Resistivity	Ω·cm	10 ¹⁴

Note: This value is for reference only and may vary slightly depending on the batch conditions.

Jundro Ceramics is a global material manufacturer that offers a wide range of advanced materials

We produce high-quality and complex products, providing significantly enhanced performance for customers engineering.

Our comprehensive service range includes material selection, precision machining, surface treatment, and quality testing to ensure that each product can perform its best practical applications.

DONGGUAN JUNDR CERAMICS TECHNOLOGY CO.LTD

Add: Room 306, Gate B, Unit 1, Block 2 South, No. 1 Yile Road, Songshan Lake, Dongguan City, Guangdong Province, China(523808)

 Tel:+86-769-82913501

 Fax:+86-769-82913801

 E-mail:info@jundro.com

 www.jundro.com